

| | |
|--|--------------------|
| Mirrors and Magnetic Pick Up Tools | Page No. 41 |
| Pick Up Magnets | |
| Inspection Mirrors | |
| Magnet Parts Trays | |
| Measuring Tools | Page No. 41 |
| Dial Gauges and Magnetic Bases | |
| Vernier Calipers | |
| Depth Gauges | |
| Squares and Combination Squares..... | |
| Levels and Protractors | |
| Thickness Gauges | |
| Calipers and Dividers | |
| Thread and Nut and Bolt gauges..... | |
| Staight Edges | |
| Tape Measures and Rules..... | |
| Safety Tools and Equipment | Page No. 41 |
| Safety Glasses and Goggles | |
| Ear Muffs | |
| Mechanic's Gloves | |
| Respirators and Dust Masks..... | |
| Safety Shields | |
| Emergency Escape Tool | |
| General Purpose Tools and Accessories | Page No. 41 |
| O-Ring Assortments | |
| Fender Covers | |
| Tow Ropes | |
| Drill Chuck Keys..... | |
| Grinding Wheel Dressers | |
| Drill Sharpeners | |
| 5 Litre Fuel Can | |
| Files, Rasps and Sets | Page No. 41 |
| Files Sets | |
| Rasps | |
| Rotary Files | |
| Fiffler and Needle Files..... | |

Blank Page

No.8796**Flex-O-Stiff Magnet**


This flexible magnet tool can be used as a rigid retrieving tool with the wire stiffening rod in place, or made completely flexible to reach around sharp corners by simply unscrewing the handle and removing the stiffening rod. 5/16"(8mm) Diameter rod permits reaching into small deep inaccessible places.

Head diameter: 5/16"(8mm) **Length:** 18"(450mm)

**No.8795****Stay-Put Flexible Magnet**

Bend to the desired shape and this magnet "stays-put". Has easy to grip knurled handle and features powerful magnet for effective grabbing power.

Head diameter: 1/2"(13mm) **Length:** 21"(535mm)

**No.8852****Adjustable Magnetic Pick Up Tool**

This full size magnet features an adjustable ball joint head that can be positioned to hold at any angle, a telescopic shaft that extends to 27" and a cushion grip insulated handle. The powerful alnico magnet will give maximum grabbing power.

Head diameter: 1/2"(13mm)
Length: 17" to 27"(430 to 690mm)

**No.7902****Small Spring Claw Pick-Up Tool**

Pick-up tool with 4 fingers designed for delicate work. Has a strong grip and fine arms.

Length: 4.1/2"(115mm)

**No.8876****'1070mm Magnetic Pick Up Tool**

Picture from Handley

No.HL5012

could be an inspection light

No.5019**1/4"Hex Telescopic Magnet with Holder**

This telescopic magnet comes with a 1/4" hex stubby bit holder. Small 9/32"(7mm) diameter magnet.

Length: 5" to 19.3/4"(125 to 500mm)

**No.8834****Bend-It-Magnet**

Put the magnet where you need it! Over 19" in length with a long lasting bendable aluminium shaft and a long life Alnico magnet. It can retrieve everything from nuts and bolts to pliers.

Head diameter: 1/4"(6mm)

Length: 19.1/4"(490mm)

**No.8797****19" Shielded Power-Lifter Magnet**

This rare earth magnet is energised for "power on demand". With magnet retracted within shrouded body there is no magnetic strength. This allows the magnet to be positioned without being attracted to any other objects. Simply depress the spring loaded button head and magnet is now energised. Magnet will lift over 1.1/2lb(680g) and the flexible shaft stays bent to access difficult areas.

Head diameter: 1/4"(6mm)

Length: 19"(480mm)

**No.8860****Magnetiser / Demagnetiser Tool**

This unique tool can be used to magnetise a screwdriver or similar tool to hold screws, or pick up a dropped nut, etc. When no longer needed, the magnetism is quickly removed by a simple wipe across the tool.


**No.8798****Flexible Spring Claw Pick Up Tool**

The flexible spring shaft allows the tool to reach into the most awkward of places. Will grip tight on objects up to 1"(25mm) diameter.

Shaft diameter: 1/4"(6mm)

Overall length: 24"(600mm)

Maximum opening: 1"(25mm)



Magnet Head Size
7/32"(5.5mm) Diameter

250g

Chrome plated brass
telescopic extension

No.8861 1/2lb Telescopic Pick-up Magnet

Ideal magnet for retrieving small parts in hard to reach situations.

Supplied with PVC injection handle.

Magnet Head Dia.: 7/32"(5.5mm)

Length: 7.1/2" to 22"(190 to 590mm)

Magnet Head Size
19/64"(7.5mm) Diameter

680g

Chrome plated brass
telescopic extension

No.8862 1.1/2lb Telescopic Pick-Up Magnet

Ideal magnet for retrieving small parts in hard to reach situations.

Supplied with PVC injection handle.

Magnet Head Dia.: 19/64"(7.5mm)

Length: 7.1/2" to 22"(190 to 590mm)

Magnet Head Size
1/2"(12.5mm) Diameter

1.6kg

6 Section stainless steel
telescopic extension

No.8863 3.1/2lb Telescopic Pick-Up Magnet

Ideal magnet for retrieving small parts in hard to reach situations. Supplied with

PVC coating, cushion grip handle,

pocket clip. Made from stainless steel.

Magnet Head Dia.: 1/2"(12.5mm)

Length: 6.3/4" to 35"(170 to 890mm)

Magnet Head Size
39/64"(15.5mm) Dia.

2.5kg

6 Section stainless steel
telescopic extension

No.8864 5.1/2lb Telescopic Pick-Up Magnet

Ideal magnet for retrieving small to medium parts in hard to reach situations. Supplied with PVC coating, cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 39/64"(15.5mm)

Length: 6.3/4" to 30"(170 to 760mm)

Magnet Head Size
39/64"(15.5mm) Dia.

3.6kg

6 Section stainless steel
telescopic extension

No.8865 8lb Telescopic Pick-Up Magnet

Ideal magnet for retrieving small to large parts in hard to reach situations. Supplied with PVC coating, cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 39/64"(15.5mm)

Length: 6.3/4" to 30"(170 to 760mm)

Magnetic shield
installed

Magnetic shield
removed

Magnet Head Size
19/64"(7.5mm) Dia.

680g

6 Section stainless
steel telescopic
extension

No.8866 1.1/2lb Shielded Telescopic Pick-Up Magnet

Ideal magnet for retrieving small parts in hard to reach situations. Shield protects magnetic forces passing through, which allows you to go down through an object without attaching on the sides. Supplied with PVC coating, cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 19/64"(7.5mm)

Shielded Dia.: 7/16"(11mm)

Length: 6.3/4" to 35"(170 to 890mm)

**Magnetic shield prevents magnet from sticking
to walls whilst entering a metal hole.**

Magnetic shield
installed

Magnetic shield
removed

Magnet Head Size
1/2"(12.5mm) Dia.

1.6kg

6 Section stainless
steel telescopic
extension

No.8867 3.1/2lb Shielded Telescopic Pick-Up Magnet

Ideal magnet for retrieving small parts in hard to reach situations. Shield protects magnetic forces passing through, which allows you to go down through an object without attaching on the sides. Supplied with PVC coating, cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 1/2"(12.5mm)

Shielded Dia.: 5/8"(16mm)

Length: 6.3/4" to 30"(170 to 760mm)

Magnetic shield
installed

Magnetic shield
removed

Magnet Head Size
39/64"(15.5mm) Dia.

2.5kg

6 Section stainless
steel telescopic
extension

No.8868 5.1/2lb Shielded Telescopic Pick-Up Magnet

Ideal magnet for retrieving small to medium parts in hard to reach situations. Shield protects magnetic forces passing through, which allows you to go down through an object without attaching on the sides.

Supplied with PVC cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 39/64"(15.5mm)

Shielded Dia.: 3/4"(19mm)

Length: 6.3/4" to 30"(170 to 760mm)

Magnetic shield
installed

Magnetic shield
removed

Magnet Head Size
39/64"(15.5mm) Dia.

3.6kg

6 Section stainless
steel telescopic
extension


No.8869 8lb Shielded Telescopic Pick-Up Magnet

Ideal magnet for retrieving small to large parts in hard to reach situations. Shield protects magnetic forces passing through, which allows you to go down through an object without attaching on the sides. Supplied with PVC cushion grip handle, pocket clip. Made from stainless steel.

Magnet Head Dia.: 39/64"(15.5mm)

Shielded Dia.: 3/4"(19mm)


Length: 6.3/4" to 30"(170 to 760mm)



No.8850

Set contains: 5Pc. Stainless Steel Mirror & Magnet Set

5 Section stainless steel telescopic handle with mirror head 90 x 50mm which extends from 170mm to 750mm. **5 Section** stainless steel telescopic handle with screw on threaded end which extends from 170mm to 650mm to *suit the following*: 33mm dia. round head flex-joint mirror 1.5lb & 8.0lb screw on magnetic head 8.0lb flex-joint screw on magnetic head



No.8898

Magnetic Bend-A-Light

High intensity super bright LED light with flexible stay-put shaft with magnets at both ends for inspections and retrieving small parts from normally inaccessible areas.
Length: 17.1/2" (445mm)

No.8898-G Replacement LED Globe
No.8898-B Replacement Battery Set



No.8871 2-In-1 Flex - Light - Magnet

Ultra thin stay-put flex shaft enables light, magnet to reach into the most inaccessible areas.

Brass and metal construction.

Magnet Head Dia.: 11/32"(9mm)

Light Diameter: 3/16"(5mm)

Powered by 2 "AA" Batteries

Overall Length: 17"(430mm)

(Batteries not included)

No.8872-G Replacement Globe



No.8870

3-In-1 Light - Magnet - Mirror

Stay-put flex shaft enables light, magnet or mirror to reach into the most inaccessible areas. Brass and metal construction.

Magnet Head Dia.: 9/16"(14mm)

Mirror Size: 1.1/8" x 2"(28 x 50mm) Oval

Light Diameter: 3/8"(10mm)

Flex Shaft Diameter: 11/32"(9mm)

Flex Shaft Length: 10"(250mm)

Powered by 2 "AA" Batteries

Overall Length: 18"(450mm)

(Batteries not included)

No.8870-G Replacement Globe



No.5109

1/4"Hex Telescopic Magnet with stubby Holder


Telescopic magnet with 9/32"(7mm) head diameter extends from 5" to 19.3/4" (125 to 502mm).

Magnet locks firmly into 1/4"Hex bit holder to reach into the most inaccessible areas.

Bit Holder Length: 2.1/8"(54mm)

Magnet Length: 5"(125mm)

Overall Length: 7.1/8"(180mm)



No.8575

Adjustable Lighted Inspection Mirror

Stay-put flex shaft enables light & mirror to reach into the most inaccessible areas. Brass and metal construction.

Mirror Size: 3.1/2" x 2"(90 x 50mm) **Light Diameter:** 3/8"(10mm)

Flex Shaft Diameter: 11/32"(9mm) **Flex Shaft Length:** 10"(250mm) Powered by 2 "AA" Batteries

Overall Length: 17"(430mm) (Batteries not included)

No.8870-G Replacement Globe



No.8872

3-In-1 Ultra Thin Flex Light - Magnet - Mirror


Ultra thin stay-put flex shaft enables light, magnet or mirror to reach into the most inaccessible areas. Brass and metal construction.

Magnet Head Dia.: 11/32"(9mm) **Mirror Size:** 1.1/8" x 2"(28 x 50mm) Oval **Light Diameter:** 3/16"(5mm) Powered by 3 "AA" Batteries

Overall Length: 24.1/2"(620mm) **Extra Extension Shaft Length:** 20"(500mm) (Batteries not included)

No.8872-G Replacement Globe





No.8570

Acrylic Inspection Mirror

The mirror head is made from tough perspex that will not shatter. Long lasting bendable shaft allows you to position the mirror in the most difficult positions and maintain the shape until you wish to change it.

Mirror size: 2" x 2" (50 x 50mm)

Length: 21" (535mm)



No.8572

Acrylic Inspection Mirror

The mirror head is made from tough perspex that will not shatter. Long lasting bendable shaft allows you to position the mirror in the most difficult positions and maintain the shape until you wish to change it.

Mirror size: 3" x 2" (75 x 50mm)

Length: 21" (535mm)



No.8567

1.1/4" Telescopic Inspection Mirror

Perfect for inspecting hidden areas, this 1.1/4" (32mm) diameter mirror swivels to almost any position. Telescopic handle extends to 19" (480mm) Supplied with handy pocket clip.

Length: 5" to 19" (125 to 480mm)



No.8569

2.1/4" Telescopic Inspection Mirror

Inspect hidden areas with this 2.1/4" (57mm) diameter mirror that swivels to almost any position. Telescopic handle extends to 15" (380mm) and has a comfort vinyl grip.

Length: 7" to 15" (180 to 380mm)



No.8571

1.1/4" Magnifying Inspection Mirror

Inspect hidden areas with this 1.1/4" (32mm) diameter magnifying mirror that swivels to almost any position.

Supplied with handy pocket clip.

Length: 8" (200mm)




No.8568

Oval Telescopic Inspection Mirror

This oval shaped inspection mirror features a telescopic handle that extends to 19" (480mm). The double ball joint head allows viewing from virtually any angle.

Supplied with handy pocket clip.

Mirror size: 2" x 1" (50 x 25mm) **Length:** 5" to 19" (125 to 480mm)



No.8575


Inspector Adjustable Lighted Mirror

This professional adjustable lighted mirror has all the following features:

- Rigid shaft, adjustable head
- 4 x Power magnified mirror
- Thumb controls for 90 degree mirror swing
- Light floods inspection area
- Powered by 2 #AA batteries (included)

Length: 18" (455mm)

Mirror size: 1.1/2" x 2.1/2" (38 x 65mm)



Storage Case (not to scale)

Stay-put shaft

Stainless steel frame

Spring actuated shaft adjusts angle of mirror head



Adjustable Angle Inspection Mirrors

No.8573 Adjustable Angle Inspection Mirror - Stainless Steel Lens

No.8574 Adjustable Angle Inspection Mirror - Glass Mirror Lens

Heavy-duty flexible stay-put shaft with spring actuated mirror angle adjustment. Enables you to change angle of mirror in confined areas.

Mirror Size: 2" x 2.3/4" (50 x 70mm)

Shaft: **Length:** 8" (200mm) **Diameter:** 7/16" (11mm) **Overall Length:** 16" (405mm)



No.5995
Magnetic Tool Holder

Holds and organises most sockets, wrenches, pliers, ratchets, screwdrivers and any other metal items. Magnet on the back of holder mounts easily to bottom of tool drawer, side of tool chest or to any flat ferrous metal surface.
Length: 17"(430mm)

Holds 20 Pounds Per Inch !



No.5993
24" Long Magnetic Tool Holder

Extra heavy-duty bar type magnetic tool holder that holds up to 20 pounds per inch. Supplied with fixing brackets, bolts and screws.
Length: 24"(610mm)

No.9606
Magnetic Earth Block

Ground your arc welder quickly and easily by attaching earth lead to the stud on the magnet. The powerful magnet will stick to pipes and flat or irregular surfaces that wouldn't accommodate lead clamps by themselves.
Diameter 3.3/4"(95mm)



No.9603
Magnetic Dish

Helps prevent loss of metal screws, nuts and other small parts. Keeps parts handy and in order for easy re-assembly. Rubber magnetic base will not scratch paintwork. Stainless steel construction.
Diameter: 6"(150mm)



No.9604
Dual Magnetic Parts Tray

Dual magnets with rubber covers will not scratch paintwork. Body made from stainless steel. Large holding capacity for holding more items and placing them in selection order.
Width: 5.1/2"(140mm)
Length: 9.1/4"(240mm)



No.9608
Four Magnet Parts Tray

Quad magnets with rubber covers will not scratch paintwork. Body made from stainless steel. Large holding capacity for holding more items and placing them in selection order.
Width: 12"(305mm) **Length:** 9.1/4"(240mm)





Windscreen Washer
Jet Cleaner



Windscreen Washer
Jet Cleaner




Windscreen Washer
Jet Cleaner



Magnetic shield
installed

Magnetic shield
removed



Extra Slim 5/32" (4mm) Head diameter.



Magnetic Pick Up Tools

8873 2.2kg Flex Head Magnetic Pick up Tool with Washer Cleaner

New design pick up magnet with extendable flexible section shaft. Includes windscreen washer jet cleaner on end cap.

Magnet Head Dia.: 7/16"(11mm)

Length: 6" to 19.3/4"(150 to 500mm)

8874 3.5kg Flex Head Magnetic Pick up Tool with Washer Cleaner

New design pick up magnet with extendable flexible section shaft. Includes windscreen washer jet cleaner on end cap.

Magnet Head Dia.: 7/16"(11mm)

Length: 6" to 19.3/4"(150 to 500mm)

8877 2.2kg Flex Head Shielded Magnetic Pick up Tool with Washer Cleaner

New design pick up magnet with extendable flexible section shaft. Includes windscreen washer jet cleaner on end cap.

Shielded protects magnetic forces passing through, which allows you to go down through the object without attaching on the sides.

Magnet Head Dia.: 7/16"(11mm) **with shield:** 5/8"(16mm)

Length: 6" to 19.3/4"(150 to 500mm)

8875 4mm 250gm Slim Head Magnetic Pick Up Tool

Extra slim pick up magnet for retrieving small parts in hard to reach situations.

Magnet Head Dia.: 5/32"(4mm)


Length: 5.1/8" to 21.5/8"(130 to 552mm)

8855 90gm Telescopic Test Hammer

90gm ball head hammer fitted to telescopic stainless steel shaft. Ideal for testing metal services for rust, fillers, etc.

Head Dia.: 3/4"(19mm)

Length: 6.3/8" to 25.3/4"(162 to 655mm)



No.6433
6\"Spring Dividers

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel.
Capacity: 8\"(200mm) **Length:** 6\"(150mm)



No.6423
8\"Spring Dividers

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel.
Capacity: 9.1/2\"(240mm) **Length:** 8\" (200mm)




No.6436
6\" Inside Caliper

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel fully polished.
Capacity: 6\"(150mm) **Length:** 7.1/2\"(190mm)



No.6437
8\" Inside Caliper

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel fully polished.
Capacity: 8\"(200mm) **Length:** 9.1/8\"(232mm)



No.6438
6\" Outside Caliper

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel fully polished.
Capacity: 6\"(150mm) **Length:** 7.1/2\"(190mm)



No.6439
8\" Outside Caliper

- **Features Quick-Adjust knurled spinner**
Made from SK-5 hardened spring steel fully polished.
Capacity: 8\"(200mm) **Length:** 9.1/8\"(232mm)




No.6435
Combination Inside / Outside Calipers

- **Features large thumbwheel centre pivot lock**
- **Standard size**
Made from SK-5 hardened spring steel.
Capacity: 11\"(280mm) **Length:** 12\"(305mm)



No.6434
Combination Inside / Outside Calipers

- **Features large thumbwheel centre pivot lock**
- **Large size**
Made from SK-5 hardened spring steel.
Capacity: 15\"(380mm) **Length:** 17\"(430mm)



Compasses with Quadrant

- No.6481 6\"(150mm) Compass with Quadrant**
Made from carbons steel, hardened and fully polished
- No.6482 8\"(200mm) Compass with Quadrant**
Made from carbons steel, hardened and fully polished



No.6461
Pocket Thickness Gauge

- For quick accurate measuring of wall thickness of tube and other parts where fine caliper points are required.
Range: 0 to 10mm **Graduations:** .01mm **Length:** 4\"(100mm)






No.6468
5" Multi-Protractor
And Circle Finder

Multi Protractor features a drill point gauge, bevel protractor and laying out angle square. Can also be use as a circle finder.
Length: 5"(125mm)



No.6469
8" 180 Degree Protractor

This 3.1/2"(90mm) semi circle stainless steel protractor is fitted with a 200mm rule with graduations to 180°. Supplied with pouch.
Length: 10"(250mm) **Rule:** 8"(200mm)



Machinist Squares

Machinist squares have a carbon steel blade and beam. Fully polished surfaces. They are available in following sizes as listed in the table below.

Individual Machinist Square Sizes:

| Part No. | Description | Length |
|----------|------------------|-------------|
| 6475 | Machinist Square | 3" (75mm) |
| 6476 | Machinist Square | 6" (150mm) |
| 6478 | Machinist Square | 8" (200mm) |
| 6479 | Machinist Square | 12" (300mm) |



No.M010
Multi-Angle Square

Tough plastic handle with three spirit levels & stainless steel protractor/rule plus scribe recessed into handle. Window shows degree of angle.
Length: 10"(250mm)



No.6440
Magnetic
Angle Finder

Measures angle of most parts such as frame angle (pitch forward or backward) for setting truck front ends. Magnetic base holds tool in place. Tool is graduated in 1/2o increments.



No.M012
Combination Square

Combination square features a quality zinc handle with spirit level and stainless steel rule. A metal scribe is recessed into the handle together with a bubble level finder. Rule has both inch & metric graduations.
Length: 12"(300mm)



No.6464
Dial Thickness Gauge

This dial thickness gauge provides an easy and accurate method for reading material thicknesses from 0 to 10mm. The dial gauge is graduated from 0 to 100 for each millimeter with a revolution counter of 1 to 10 millimeter.
Range: 0 to 10mm
Graduations: 0.01mm



No.6477
8" Universal T Bevel

This universal 8"(200mm) universal T bevel features a stainless steel rule with wooden handle. Fully adjustable with full polish finish.
Length: 8"(200mm)




No.6480

3 in 1 Professional Combination Square

This heavy duty 3 in 1 professional combination square has cast steel bodies with a stainless steel satin chrome rule 12" (300mm). Graduations in inches and millimeters. All parts are housed in a sturdy metal case.

Range: 0 to 12"(0 to 300mm)



Stainless Steel Rules

Made from stainless steel with satin finish for easy reading & long lasting rust resistance. Graduations: 1/64" & 0.5mm.

| Part No. | Description | Length | Width |
|----------|----------------------------------|--------------|-------------|
| 6425 | Double Side Stainless Steel Rule | 6" (150mm) | 3/4" (19mm) |
| 6426 | Double Side Stainless Steel Rule | 12" (300mm) | 1" (25mm) |
| 6427 | Double Side Stainless Steel Rule | 24" (600mm) | 1" (25mm) |
| 6428 | Double Side Stainless Steel Rule | 40" (1000mm) | 1" (25mm) |



No.6483

6" Pro-Contour Gauge

This 6"(150mm) pro-contour gauge has a zinc plate finish body with both inch and metric graduations. The 3.1/4"(82mm) pins made of stainless steel. Both internal and External curves are obtain by reading either side of the contour of the gauge.

Pin Length: 3.1/4"(82mm)

Length: 6"(150mm)



No.6463

Pocket Slide Rule

Stainless steel slide rule, measures inside & outside.

Range: 3" & 75mm

Graduations: 1/32" & 1.0mm



No.PT5019

5M/16ft Tape Measure

Professional power tape is durable, comfortable easy to hold. "Top-stop" secures tape in place. Special shock absorbing bumper with 3 rivets protects the tape from damage. Tough chrome plated ABS case. Both inch and metric measurements clearly indicated.

Tape width: 3/4"(19mm)



No.PT8025

8M/26ft Tape Measure

Professional power tape is durable, comfortable easy to hold. "Top-stop" secures tape in place. Special shock absorbing bumper with 3 rivets protects the tape from damage. Tough chrome plated ABS case. Both inch and metric measurements clearly indicated.

Tape width: 1"(25mm)



No.6431

Universal Depth Gauge

Easy to read gauge with stainless steel rule and depth rod. Makes precise depth measurements in small holes & slots.

Also doubles as a protractor.

Permits easy setting of protractor angle to 30°, 45° & 60° settings on both sides. Measures all three adjustments on carburetors accurately.

1. Float level

2. Float Drop

3. Pump rod travel

Dual Graduations: 1/32" & 1.0mm

Length: 6"(150mm)



No.6455

Imperial Dial Indicator & Base Set

Used for precise adjustments on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.
Combination #6457 & #6459 gauge and base set.



No.6456

Metric Dial Indicator & Base Set

Used for precise adjustments on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.
Combination #6458 & #6459 gauge and base set.



Readings
0.001mm
0.00005 Inch

No.MT258 Digital 55mm Dial Indicator

Super fine digital dial indicator with resolution of 0.001mm and 0.00005"
1"(25mm) Travel auto power off.
Zero setting at any position.
Metric / Inch conversion system with multi-function button, easy for maximum or minimum measuring.
Gauge Diameter: 2.1/4"(55mm)
Travel: 1"(25mm)
Resolution: 0.001mm and 0.00005"

Laser Power Switch Spirit Bubble Digital Inclinator Spirit Bubble Angular Measurement Vertical Base Level

Caution: Avoid direct eye exposure to laser beam



No.P6552

Digital Angle Meter with Horizontal & Vertical Levels

- Two bubble level for vertical and horizontal checkout
- Adjustable laser indicator available in spot and line shape
- Operating range: 0° to 360°C

Range: 0 - 360°

Display : 6 digital display on LCD

Horizontal Base Level

- Angle measurement
- LCD display: digital data & % (tag)
- Operates on A 6F22, 9V battery

Laser pointing accuracy: ± 1mm per metre

Caution: Avoid direct eye exposure to laser beam



No.P7471

4in1 Ultrasonic Rangefinder Level & Angle Meter with Laser

- Ultrasonic rangefinder measures range: 2ft - 50ft (0.6m - 15m)
- Adjustable built in laser available in spot and line shape
- Conversion unit for feet, inches and metres
- Automatic power off time: after 30 seconds of inactivity
- Power supply: A 6F22, 9V battery


- Bubble level for horizontal checkout
- Angle measurement
- Length / Area / Volume measurement
- Data computation, storage, recall



No.P6353

4in1 Metal / Voltage / Stud / Moisture Tester


- Wire, metal and stud detection, moisture metre
- Tests wood moisture from 8% to 22%
- Automatic and manual detection with buzzer indicator
- Fast, accurate and easy to read by LED display
- Power supply: requires one 6F22, 9V battery



No.6474
35 x 16 x 600mm Precision Straight Edge

Used for checking warpage on engines and machine parts, etc. Made from stainless steel for long lasting rust resistance. Supplied in metal storage case.

Depth: 1.3/8"(35mm)
Width: 5/8"(16mm)
Length: 23.5/8"(600mm)



Straight Edges

Used for checking warpage on engines and machine parts. Made from stainless steel for long lasting rust resistance. Supplied with safety cover for machined edge.

| Part No. | Description | Length | Width |
|----------|---------------|-------------|---------------|
| 6470 | Straight Edge | 18" (450mm) | 1.1/2" (38mm) |
| 6471 | Straight Edge | 24" (610mm) | 2" (50mm) |
| 6472 | Straight Edge | 40"(1000mm) | 2.1/4" (58mm) |

No.MT147
50mm to 160mm
Dial Bore Gauge

Measure bores from 50 to 160mm. Has a unique self centering measurement head. For quick checking of diameters, roundness, taper, wear and allied parameters of bores at any desired depth, with direct reading on the dial gauge. Features self centering to ensure maximum measuring accuracy with minimum operator skill, hardened and ground contact point with ball end anvils, quick setting treaded type anvils covering 50 to 160mm range in 10mm intervals.



No.MT171
3mm - 13mm
Small Hole Bore Gauge Set

Sizes: 3 mm (0.125") to 13 mm (0.5"). They require a slightly different technique to the telescopic gauges, the small hole gauge is initially set smaller than the bore to be measured. It is then inserted into the bore and adjusted by rotating the knurled knob at the base, until light pressure is felt when the gauge is slightly moved in the bore.

Individual Sizes:

- A:** 3 mm (0.125") to 5 mm (0.200") Small Hole Bore Gauge
- B:** 5 mm (0.200") to 7.5 mm (0.300") Small Hole Bore Gauge
- C:** 7.5 mm (0.300") to 10 mm (0.400") Small Hole Bore Gauge
- D:** 10 mm (0.400") to 13 mm (0.500") Small Hole Bore Gauge



No.MT170
8mm - 50mm Telescopic Gauge Set

These gauges are used to measure a bore's size, by transferring the internal dimension to a micrometer. Gauges are locked by twisting the knurled end of the handles, this action is performed to exert a small amount of friction on the telescopic portions of the gauge. Once gently locked to a size slightly larger than the bore, the gauges are inserted at an angle to the bore and slowly brought to align themselves radially, across the hole. This action compresses the two anvils where they remain locked at the bores dimension after being withdrawn. The gauge is then removed and measured with the aid of a micrometer.





Travel 3mm

No. MT126-41

41mm Dial Indicator Gauge

Used for precise adjustment settings on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 3mm

Graduations: .001mm

Readings: 0 to 3mm

Diameter: 41mm

Shank: 5/16"(8mm)

Mounting: Rear lug



Travel 8mm

No. MT231-41

41mm Dial Indicator Gauge

Used for precise adjustment settings on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 8mm

Graduations: .01mm

Readings: 0 to 8mm

Diameter: 41mm

Shank: 5/16"(8mm)

Mounting: Rear lug



Travel 10mm

No. MT126-55

60mm Dial Indicator Gauge

Used for precise adjustment settings on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 10mm

Graduations: .01mm

Readings: 0 to 10mm

Diameter: 60mm

Shank: 5/16"(8mm)

Mounting: Rear lug



Travel 25mm

No. MT256-60

60mm Dial Indicator Gauge

Used for precise adjustment settings on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 25mm

Graduations: .01mm

Readings: 0 to 25mm

Diameter: 60mm

Shank: 5/16"(8mm)

Mounting: Rear lug



Travel 1 Inch

No. 6457

Dial Indicator Gauge (Imperial)

Used for precise adjustments on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 1.00"

Graduations: .001"

Readings: 0 to .100"

Diameter: 2.1/4"(60mm)

Shank: 3/8"

Mounting: Rear lug



Travel 25mm

No. 6458

Dial Indicator Gauge (Metric)

Used for precise adjustments on many automotive applications, checking clearances, tolerances on engines, transmissions and all assemblies where accuracy is needed.

Travel: 25mm

Graduations: .01mm

Readings: 0 to 2mm

Diameter: 2.1/4"(60mm)

Shank: 3/8"

Mounting: Rear lug



No. 6460 Standard Magnetic Base

Three adjustable arms enable gauge to be positioned in any required position for positive fixing. Heavy-duty switch on-off magnetic "V" base that grips onto flat or curved surfaces.

Universal gauge mounting bracket.

Magnetic Strength: 170lb.(75kg)



No. 6459 Flex Arm Magnetic Base

Features an infinitely adjustable 12.1/2" (320mm) flexible arm with heavy-duty switch on-off magnetic "V" base that grips onto flat or curved surfaces.

Universal gauge mounting bracket.

Magnetic Strength: 170lb.(75kg)













No. 6462 Hydraulic Lock Magnetic Base

Firm and solid fixing of all five joints is achieved by the tightening of just one knob. Fits dovetail, 3/8" or 8mm dial indicator stems. Multiple joint for instant positioning and fixing.

Reach: 10"(250mm)

Magnetic Strength: 180lb.(80kg)

| | |
|--|---|
|  <p>No.6465</p> <p>150mm Stainless Steel Vernier Caliper</p> <ul style="list-style-type: none"> • Metric & Imperial graduations • Satin chrome finish • Four-way measuring Measures inside, outside, depth & step. <p>Range: 0" to 6" & 0 to 150mm Graduations: 1/128" & 0.05 millimetre</p> <p>Overall length: 6"(150mm) Supplied in sturdy pouch.</p> | <p><i>Dual Vernier Calipers With Fine Adjustment</i></p>  <p>No.MT002-150</p> <p>6"(150mm) Vernier Caliper</p> <p>Range: 0" to 6" & 0 to 150mm Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> |
| <p><i>Made of Carbon Fibre Composite</i></p>  <p>No.MT149</p> <p>150mm Digital Vernier Caliper</p> <p>Electronic digital vernier caliper made from extra strong carbon fibre composite. Measures inside, outside, depth & step.</p> <p>Range: 0" to 6" & 0 to 150mm Graduations: 0.01" & 0.1 millimetre</p> <p>Overall length: 6"(150mm) Supplied on backing card.</p> | <p><i>Dual Vernier Calipers With Fine Adjustment</i></p>  <p>No.MT002-200</p> <p>8"(200mm) Vernier Caliper</p> <p>Range: 0" to 8" & 0 to 200mm Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> |
| <p>Metric Dial Vernier Calipers</p> <div>  <p>No.MT020-150</p> <p>150mm Dial Vernier Caliper</p> <p>Range: 0" to 6" & 0 to 150mm</p> <p>Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> </div> <div>  <p>No.MT020-200</p> <p>200mm Dial Vernier Caliper</p> <p>Range: 0" to 8" & 0 to 200mm</p> <p>Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> </div> | |
| <p>ABS Digital Vernier Calipers</p> <p>ABS digital vernier calipers are made from stainless steel, hardened and feature four button control. 1: Red = power on/off. 2: Green = metric / inches in any position. 3: Orange = Origin to zero setting. 4: Yellow = ABS/O, Relative zero point and absolute valve interchange. Data output interface (to printer or computer). Resolution: 0.01mm / 0.001" Power: 1 x 1.5 volt button cell battery (CR44). Supplied in a storage case with spare battery with full operating instructions.</p> <div>  <p>No.MT028-300</p> <p>300mm ABS Digital Vernier</p> <p>Range: 0" to 8" & 0 to 200mm</p> <p>Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> </div> <div>  <p>No.MT028-200</p> <p>200mm ABS Digital Vernier</p> <p>Range: 0" to 8" & 0 to 200mm</p> <p>Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> </div> <div>  <p>No.MT028-150</p> <p>150mm ABS Digital Vernier</p> <p>Range: 0" to 8" & 0 to 200mm</p> <p>Graduations: 1/1000" & 0.01mm</p> <p>Made from Stainless Steel and Supplied in a storage case.</p> </div> <div>  <p>No.MT991</p> <p>Digital Disc Brake Rotor Gauge</p> <p>To check wear, thickness and score depth on disc brake rotors. External / depth measurement, mm / inch interchange button, zero setting at any position. Range: 0 to 150mm / 0 to 6" Throat Depth: 90mm / 3.5" Resolution: 0.01mm / 0.0005"</p> </div> | |



No.8035

Screw And Weld Measuring Gauge

Screw and weld gauge is graduated in metric and imperial on each side. Enables to quickly measure screw, bolt and other rod sizes accurately. Includes 3" and 75mm rule on the side and measures gauge sizes from 1 to 11mm and imperial equivalents.

Overall Length: 4"(100mm)

Gauge Sizes: 1 to 11mm

Rule: 3" (75mm)



No.6445

Drill Measuring Gauge

Drill measuring gauge is made from stainless steel with all markings permanently etched onto the face. Sizes cover 1/16" to 1/2" in 64ths. and decimal equivalents are included.

No.6442

18Pc. Angle Gauge Measuring Set

18Pc. angle gauge set covers all angles from 5° to 90° in 5° increments.

Made from high carbon steel and supplied in vinyl wallet.



No.6443

26Pc. Radius Gauge Set

26Pc. radius gauge set covers all radii from 0.5mm to 13mm in 5mm increments.

Made from high carbon steel and supplied in vinyl wallet.



No.6446

Metal Case Counter

Manual counter to record all types of counts up to 9999.



No.6422

6" Pocket Clip Ruler

Handy pocket clip rule with metric and imperial graduations made from stainless steel.

Length: 6"(150mm)



No.6444

32Pc. Radius Gauge Set

32Pc. radius gauge set covers all radii from 7.5mm to 15mm in 5mm increments.

Made from high carbon steel and supplied in vinyl pouch.


Screw Cutting Gauge

Screw cutting gauge gives a range of angles. 60° for USA (UNC and UNF) and International metric.

55° Whitworth.

47.5° British Association.

14.5° Acme threads.



No.6451

Bulls-Eye Surface Level

- Ideal for leveling in more than one plane

Base Diameter: 1.3/4"(45mm)

Diameter Lens: 1"(25mm)



Magnetic Angle Holders

Magnetic block angle holders are ideal for holding metal structures for welding or assembly.

No.6441-S Magnetic Block Holder

120mm long x 82mm width x 15mm thick

No.6441-M Magnetic Block Holder

158mm long x 102mm width x 19mm thick

With centre hole





**No.7331
Safety Glasses**

Clear (With side protection) Made from high impact resistant plastic. Wrap around style with top and side protection shields. Arms have lanyard holes. One size fits all. Will fit over prescription glasses.



**No.7332
Safety Glasses**

Black (With side protection) Made from high impact resistant plastic. Wrap around style with top and side protection shields. Arms have lanyard holes. One size fits all. Will fit over prescription glasses.



**No.7333
Safety Glasses**

Yellow (With side protection) Made from high impact resistant plastic. Wrap around style with top and side protection shields. Arms have lanyard holes. One size fits all. Will fit over prescription glasses.



**No.7334
Safety Glasses**

Green (With side protection) Made from high impact resistant plastic. Wrap around style with top and side protection shields. Arms have lanyard holes. One size fits all. Will fit over prescription glasses.



**No.7036
Protective Safety Glasses**

Specially designed, OSHA-approved safety glasses have coated plastic lenses to help prevent scratching. Top and side shields assist in preventing eye injury to the wearer.



**No.7035
Anti-Fog Safety Goggles**

Flexible coverall goggles are molded from form fitting vinyl, which provides the highest degree of protection and wearer comfort. They weigh only 2 ounces (56gms) and are large enough to fit over prescription glasses. Specialised ventilation supplies proper air circulation. The polycarbonate lens is clear for sharp vision.



**No.7338
Ear Muffs**

Offers exceptional comfort and attenuation over the full frequency range. Made from Polyethylene and are fully adjustable.



**No.7038
Flip-Up Safety
Welding Goggles**

Flip-up lens feature allows you to see when torch is not welding. Soft yet rugged frame will fit over prescription glasses.



**No.SE1140
Welding Goggles**

Indirect ventilation, soft flexible vinyl frame, 2" x 4.1/4" polycarbonate #5 green shade flip front lens. Switch from welding for easy inspection.
Compliance: CE EN166, ANSI Z87.1, CSA Z94.3



No.7330 Non Toxic Particle Dust Mask

(Packet of 50)

Made from non-woven cloth with elastic-band and a press aluminium nose support.



No.SE1510 Half Mask Respirator

Dual cartridges with soft pliable rubber face piece & durable adjustable elastic headbands. Deep chin cup for a roomy comfortable seal and easy exhaling.



Cartridges sold separately.

No.SE153B Dust Cartridges

(2 cartridges per pack)

Anti dust, mist, fumes and asbestos.



No.SE153C Chemical Cartridges

(2 cartridges per pack)

Anti organic vapors and for paint spray.



*For commercial
passenger vehicles*



No.GH3 Emergency Escape Tool

This glass breaking hammer with inbuilt carbide tip is designed to smash glass with ease. Has an inbuilt slide out cutter for cutting through the seat belt. Includes a small light to see in case of an emergency.

Overall Length: 10"(250mm)

No.7759 Electronic Ear Defenders

Electronic ear defenders filter out noise above 85 decibels. Normal hearing below 85 decibels can still be heard. For example operator instructions and safety commands. Adjustable head earphones offer exceptional comfort and attenuation over the 85 decibels frequency range. Batteries included.



*Machine
washable*

No.SE2510 Kevlar Safety Gloves

Heat resistant Kevlar fibre provides better protection against heat, slashes, scrapes, cuts and abrasions. Good air circulation to keep hands dry. Lightweight, washable, reversible and durable.



*Machine
washable*

No.G7730 Pig Skin Mechanics Gloves

Quality treated pig skin gloves give a comfortable second skin fit.

No.G7730M Medium Size Pig Skin Mechanics Gloves

No.G7730L Large Size Pig Skin Mechanics Gloves

No.G7730XL Extra Large Size Pig Skin Mechanics Gloves



*Machine
washable*

Spandex Mechanics Gloves

Quality double stitched Spandex gloves give a comfortable second skin fit. Mechanics favourite gloves keeps hands clean and protected.

No.G7700M Medium Size Spandex Mechanics Gloves

No.G7700L Large Size Spandex Mechanics Gloves

No.G7700XL Extra Large Size Spandex Mechanics Gloves



*Machine
washable*


Mechanics Pro Gloves

Features perforated finger fourchettes for comfort. Reinforced padded palm, thumb and fore-finger to cushion impact and vibration.

No.G7711M Medium Size Mechanics Pro Gloves

No.G7711L Large Size Mechanics Pro Gloves

No.G7711XL Extra Large Mechanics Pro Gloves



No.999 Wire Bag Twister

Industrial quality, designed for fast and efficient closing of sack ties or concrete reinforcing steel wires. Accurately machined spring return spiral spindle with wear resistant bronze sleeve. Moulded ribbed plastic handle.
Length: 12"(305mm)



No.SC100 T&E Seat Covers

Heavy-duty cotton material protects seat surface from getting soiled during service by mechanic. Simply slip over the back of the seat and adjust. One size fits all seats.



No.8660

"Hang Tough" Fender Cover

Fits cars and trucks, including front wheel drive vehicles with narrow fenders. Protects vehicle painted surfaces from chemicals and scratching while service is performed, without falling off the vehicle. Multi-strand elastic cord for long life. Thin diameter hook can be bent to allow attaching cover conveniently under hood. Superior to magnetic or foam backed covers. A fender cover that spends more time on the fender than on the floor. Cleans with soap or mild solvent.
Size: 27" x 36"(685 x 915mm)



No.995 2 Ton Steel Wire Tow Rope

4 Metre long wire tow rope with swaged loop ends and two alloy steel shackles. Protective PVC coating on wire rope.
Capacity: 2 Ton
Length: 13 ft (4m)



**Professional Quality
"Nitrile 70" O-Rings**

No.OR105 386Pc. O-Ring Assortment Set HNBR Series

NHBR series o-rings are designed for use in air conditioning systems & fittings. They are made from professional quality Nitrile 70 material.

| Actual Size | | Actual Size | | Actual Size | |
|-------------|------|-------------|------|-------------|------|
| I.D. | W. | I.D. | W. | I.D. | W. |
| 4.47 | 1.78 | 7.65 | 1.78 | 13.95 | 2.62 |
| 4.50 | 1.50 | 9.25 | 1.78 | 13.90 | 1.80 |
| 5.57 | 1.78 | 10.62 | 1.78 | 15.54 | 2.62 |
| 6.07 | 1.78 | 10.80 | 2.40 | 17.17 | 1.78 |
| 6.75 | 1.78 | 11.00 | 2.00 | 18.72 | 2.62 |
| 6.80 | 1.60 | 13.80 | 2.40 | 20.22 | 3.53 |



No.996 3 Ton Steel Wire Tow Rope

4 Metre long wire tow rope with swaged loop ends and two alloy steel shackles. Protective PVC coating on wire rope.
Capacity: 3 Ton
Length: 13 ft (4m)



No.OR100 386Pc. O-Ring Assortment Set NBR Series

NBR series o-rings are designed for general purpose use. They are made from professional quality Nitrile 70 material.

| Actual Size | | Actual Size | |
|-------------|------|-------------|------|
| I.D. | W. | I.D. | W. |
| 2.90 | 1.78 | 20.22 | 3.53 |
| 3.69 | 1.78 | 21.82 | 3.53 |
| 4.47 | 1.78 | 23.39 | 3.53 |
| 5.29 | 1.78 | 25.00 | 3.53 |
| 6.07 | 1.78 | 26.57 | 3.53 |
| 7.65 | 1.78 | 28.17 | 3.53 |
| 9.25 | 1.78 | 29.57 | 3.53 |
| 9.19 | 2.62 | 31.34 | 3.53 |
| 10.77 | 2.62 | 32.92 | 3.53 |
| 12.37 | 2.62 | 34.52 | 3.53 |
| 13.95 | 2.62 | 36.10 | 3.53 |
| 15.54 | 2.62 | 37.70 | 3.53 |
| 17.12 | 2.62 | 37.47 | 5.34 |
| 18.72 | 2.62 | 40.65 | 5.34 |
| 18.64 | 3.53 | 43.82 | 5.34 |

**Professional Quality
"Nitrile 70" O-Rings**






No.1885
Cargo Support Bar

Tubular adjustable bars feature swivel support pads with left and right hand threads. A simple twist will quickly adjust the length to hold cargo loads in place. Can also be used as an upright prop. Aluminium construction with twist locking action. Quickly adjust to size to securely hold load in place. Can also be used as an adjustable prop to support and align objects in any plane.

Adjustable length: 37"to 62"(940mm to 1580mm)

Bar diameter: 1.1/8"(28mm)



No.1887
Truck Cargo Support Bar

Tubular adjustable bars feature swivel support pads with left and right hand threads. A simple twist will quickly adjust the length to hold cargo loads in place. Can also be used as an upright prop. Chrome plated steel construction with locking detent pin adjustment. Quickly adjust to size to securely hold load in place. Can also be used as an adjustable prop to support and align objects in any plane.

Adjustable length: 40"to 74"(1015mm to 1880mm)

Bar diameter: 1.1/8"(28mm)

Drop Forged "G" Clamps

Drop forged and heat treated for maximum strength. Hardened centre screw for long-life, greater strength to resist warping. Large anvils give greater gripping contact. Ball-jointed impact resistant pressure pad.



No.M100
4\"/>




No.M150
6\"/>



No.M200
8\"/>



No.M300
12\"/>



No.SP490
90° Corner Clamp

Self centering 90° angle adjusting screw clamps material up to 2.3/4"(70mm) to be held for 45° mitre. Use for clamping items at 90° angle.

All metal construction.

Opening :

2.3/4" x 2.3/4" x 1.3/8"(70x70x35mm)



No.PWC260
Soft Jaw Ratchet locking clamp

This soft jaw clamp offers a variable clamping force to secure the workpiece without damage to the surface. Ratchet mechanism allows to user to control the force needed. Flexible jaw will hold the workpiece without slipping.

Quick and easy push button release system.

Length: 10"(25mm)

Capacity: 0 to 2.7/16"(0 to 62mm)

4 Way Master Chuck Keys

Four sizes on each key will fit most drill chucks used by drill manufacturers today.

R103 Small 4 way Master Chuck Key
Sizes: #1, #2, #3, #4, (Opens 86 different chucks)

R104 Large 4 way Master Chuck Key
Sizes: #5, #6, #7, #8 (Opens 127 different chucks)



R103



R104

Hand Power Pullers/Winches

High quality ratchetting cable pullers available in tonnages from one to four ton capacity. All feature leverage of 16:1 and can be used for all types of pulling, lifting, straightening and tensioning jobs. They are lightweight, yet a practical winch for all applications.

HP111 1 Ton Hand Power Puller


Capacity: 1Ton(1000kg)
: 10ft (3.05m) Pull/Lift. Fitted with 2 hooks.
Fitted with 3/16"(5mm) Aircraft Cable.



HP111

HP117 2 Ton Hand Power Puller


Capacity: 2Ton(2000kg)
: 12ft (3.66m) Pull/Lift. Fitted with 2 hooks.
Fitted with 3/16"(5mm) Aircraft Cable.



HP117

HP123 2 Ton Hand Power Puller

I Double gear & pawls, A1 type switch handle
Capacity: 2Ton(2000kg)
: 10ft (3.05m) Pull/Lift Fitted with 3 hooks.
Fitted with 3/16"(5mm) Aircraft Cable.



HP123

HP147 4 Ton Hand Power Puller

I Double gear & pawls, A1 type switch handle
Capacity: 4Ton(4000kg)
: 10ft (3.05m) Pull/Lift Fitted with 3 hooks.
Fitted with 1/4"(6mm) Aircraft Cable.



HP147

HPW211 1 Ton Webbing Power Puller

I Heavy-Duty 30ft(9 Metre) Webbing
I Double gear & pawls, A1 type switch handle
Capacity: 1Ton(1000kg)
: 30ft(9m) Pull/Lift Fitted with 2 hooks.
Fitted with Heavy-Duty Polyester Webbing

Caution:1: Check cable regularly for fraying or broken strands.

2: Do not pull cable over or around corners.


3: Do not wrap cable around objects and allow it to pull back on itself.

4: Be sure not to exceed tonnage rating.

5: Do not use cheater bars on the handle.

6 Do not operate puller with less than three wraps of cable on the spindle.

7: Always make sure there is positive engagement of the puller hook to the load.



SWITCH



Patented



HPW211

POLYESTER WEBBING



No. RT2006
5 Litre Fuel Can

Extra strong versatile fuel container with screw on flexible spout. Made from tough PE material. The ideal container for emergency and storage of mixed fuels.

Capacity: 1.1 gallons (5 litres)



No. RT2010
10 Litre Fuel Reserve Tank

Extra strong versatile fuel container with screw on flexible spout. Made from tough PE material. The ideal container for emergency and storage of mixed fuels.

Capacity: 2.2 gallons (10 litres)



No. RT2020
20 Litre Fuel Reserve Tank

Extra strong versatile fuel container with screw on flexible spout. Made from tough PE material. The ideal container for emergency and storage of mixed fuels.

Capacity: 4.4 gallons (20 litres)



GWD10

Grinding Wheel Dresser Huntington #1

Solid cast iron handle with multiple steel star wheels for dressing the face of all types and sizes of grinding wheels.

Length: 10.1/4" (260mm)

GWD21 Replacement Wheels for #GWD10
Diameter: 1.1/2" (38mm)



GWD12

Grinding Wheel Dresser Huntington #1

Solid cast iron handle with multiple steel star wheels for dressing the face of all types and sizes of grinding wheels.

Length: 12.1/4" (310mm)

GWD22 Replacement Wheels for #GWD12
Diameter: 2.1/4" (57mm)



No. LP91
Revolving Head
Leather Punch

This high quality patented leather punch will punch holes in leather and gasket materials from 2mm to 4.5mm diameter. Its double action leverage design requires 65% less hand power.

Revolving Head Sizes: 2mm, 2.5mm, 3mm, 3.5mm, 4mm, 4.5mm
Length: 9" (230mm)

**No more lost small parts
in the cleaning tank**

5996
Small Parts
Cleaning Basket



Container provides a place for small parts; such as carburettor, fuel injection or transmission parts, to prevent loss in a parts cleaner. Basket is made of durable wire mesh with a galvanised steel cover that slides tightly over basket. Includes a hook to conveniently hang basket into solution for soaking parts.



5990
Magnetic Impact Wrench & Socket Holder


Two powerful magnets fix this wrench holder securely to any metal surface. e.g: workshop hoist, bench, etc. Holds your impact wrench at working height together with for deep impact sockets. Saves time, effort and keeps your tools off the floor.

Length: 14" (355mm)



Weights only
2.2kgs

180kgs
Capacity



No. A600
Dolly - Kneeler - Sitter

Five swivel casters, super comfort centre pad. Reinforced moulded dolly. Great work seat - kneeling pad - dolly truck.

Maximum Capacity: 180kgs

Length: 600mm **Width:** 400mm

A1001 10Pc. Arro Eyelets Set

Unique set of ten plastic self sealing eyelets that have a rubber seal and by snapping the two sections together they will cut the canvas or plastic sheeting to make the required eyelet hole. Tap lightly with a hammer to lock into position and make a proper seal.

Outside diameter: 30mm

Inside diameter: 12mm

Ten pieces on backing card.



AAABATTERY AAA Battery

AABATTERY AA Battery



Blank Page

No.F2208**8" Mechanic's File Set**

Set includes 5 x 8"(200mm) files:

- ▲ Slim Taper File
- ▬ Flat File
- ◐ Half Round File
- Round File
- Square File

Supplied in vinyl pouch.

**No.F2210****10" Mechanic's File Set**

Set includes 5 x 10"(250mm) files:

- ▲ Slim Taper File
- ▬ Flat File
- ◐ Half Round File
- Round File
- Square File

Supplied in vinyl pouch

**Flat Bastard Files**

- No.F1008 8" Flat Bastard File
Length: 8"(200mm)
- No.F1010 10" Flat Bastard File
Length: 10"(250mm)
- No.F1012 12" Flat Bastard File
Length: 12"(300mm)

Flat 2nd Cut Files

- No.F1208 8" Flat 2nd Cut File
Length: 8"(200mm)
- No.F1210 10" Flat 2nd Cut File
Length: 10"(250mm)
- No.F1212 12" Flat 2nd Cut File
Length: 12"(300mm)

Half Round Bastard Files

- No.F1408 8" Half Round Bastard File
Length: 8"(200mm)
- No.F1410 10" Half Round Bastard File
Length: 10"(250mm)
- No.F1412 12" Half Round Bastard File
Length: 12"(300mm)

Half Round 2nd Cut Files

- No.F1508 8" Half Round 2nd Cut File
Length: 8"(200mm)
- No.F1510 10" Half Round 2nd Cut File
Length: 10"(250mm)
- No.F1512 12" Half Round 2nd Cut File
Length: 12"(300mm)

Millsaw Bastard Files

- No.F1308 8" Millsaw Bastard File
Length: 8"(200mm)
- No.F1310 10" Millsaw Bastard File
Length: 10"(250mm)
- No.F1312 12" Millsaw Bastard File
Length: 12"(300mm)

Millsaw 2nd Cut Files

- No.F1608 8" Millsaw 2nd Cut File
Length: 8"(200mm)
- No.F1610 10" Millsaw 2nd Cut File
Length: 10"(250mm)
- No.F1612 12" Millsaw 2nd Cut File
Length: 12"(300mm)

Round Bastard Files

- No.F1708 8" Round Bastard File
Length: 8"(200mm)
- No.F1710 10" Round Bastard File
Length: 10"(250mm)
- No.F1712 12" Round Bastard File
Length: 12"(300mm)

Round 2nd Cut Files

- No.F1808 8" Round 2nd Cut File
Length: 8"(200mm)
- No.F1810 10" Round 2nd Cut File
Length: 10"(250mm)
- No.F1812 12" Round 2nd Cut File
Length: 12"(300mm)

Square Bastard Files

- No.F2008 8" Square Bastard File
Length: 8"(200mm)
- No.F2010 10" Square Bastard File
Length: 10"(250mm)
- No.F2012 12" Square Bastard File
Length: 12"(300mm)

Square 2nd Cut Files

- No.F2108 8" Square 2nd Cut File
Length: 8"(200mm)
- No.F2110 10" Square 2nd Cut File
Length: 10"(250mm)
- No.F2112 12" Square 2nd Cut File
Length: 12"(300mm)

**No.F5012****10Pc. Riffler Needle File Set**


Special shaped curved ends on these small files are used to clean and smooth out grooved surfaces on machine components and die blocks used in tool making.
Supplied in vinyl wallet.

Slim Taper Files

- No.F2304 4" Slim Taper File
Length: 4"(100mm)
- No.F2306 6" Slim Taper File
Length: 6"(150mm)
- No.F2308 8" Slim Taper File
Length: 8"(200mm)
- No.F2310 10" Slim Taper File
Length: 10"(250mm)

Half Round Rasp

- No.F2408 8" Half Round Rasp
Length: 8"(200mm)
- No.F2410 10" Half Round Rasp
Length: 10"(250mm)
- No.F2412 12" Half Round Rasp
Length: 12"(300mm)
- No.F2414 14" Half Round Rasp
Length: 14"(350mm)

**No.F5010****10Pc. Needle File Set**

Set of 10 individual small files with different shaped edges for cleaning, dressing and sharpening small parts etc.



Blank Page

| | |
|--|--------------------|
| Punches, Chisels and Pry Bars | Page No. 41 |
| Pin, Drift, Taper, Centre Punches and Sets | |
| Heavy Duty Punches | |
| Pry and Roll Head Bars | |
| Number and Letter Punches..... | |

| | |
|----------------------------|--------------------|
| Hammers | Page No. 41 |
| Ball Pien Hammers | |
| Sledge Hammers | |
| Soft Face Hammers | |
| Dead Blow Hammers | |
| Copper Brass Hammers | |
| Hammers Miselaneous | |
| Hammer Handles | |