

Pneumatic ToolsPage No. 41

| | |
|---|--|
| Pneumatic Chisels and Retaining Chucks | |
| Air Dust Guns | |
| Air Sand Blasting, Cleaning Caulking and Sealant Guns | |
| Air Spray Guns | |
| Air Compressor Tanks..... | |
| Air impact Wrenches, Drills and Grinders | |
| Air Compressor Hose and Fittings | |
| Hose Crimping Tools | |
| Air Compressor Filter, Regulator and Lubricators..... | |
| Pneumatic Oil Pumps | |



1972



1973



1974




1975



1978



1980



1981



1979



1998



1996



1985



1986

Pneumatic Panel Cutters

Premium quality panel cutters are guaranteed to give long service.

1972 Double Cut Body Ripper

Double sided cutting edges extend life of this pneumatic panel cutter designed to use with an air hammer.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

1973 Radius Panel Cutter

Has the exceptional ability to cut a tight radius fast and smooth.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

1974 Slotted Panel Cutter

This panel cutter leaves a clean smooth edge with the cut curling up through the slot in the middle.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

1975 Spot Weld Breaker

Ideal tool for cutting spot welds. Bevelled edge separates panels and spot weld is then caught in "V" section to break it cleanly.

Also works well for cutting moldings and rivets.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

Pneumatic Air Chisels

Designed to cut nuts, bolts and for use on jobs where a general purpose chisel is required.

1978 Cold Chisel 6"

Length: 6"(150mm)

Shank diameter: .401"Parker shank

1980 Cold Chisel 10"

Length: 10"(255mm)

Shank diameter: .401"Parker shank

1981 Cold Chisel 18"

Length: 18"(460mm)

Shank diameter: .401"Parker shank

1979 Rivet & Bolt Cutter

Bevelled on one side for flush cutting of rivets, bolts etc.

The correct tool for removal of rivetted Ford ball joints from control arms.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

1998 Scraper Chisel

Use for removing gaskets, rust, undercoating, and all jobs where a wide scraper chisel is required.

Shank diameter: .401"Parker shank

Length: 8"(200mm) *Width:* 1.1/8"(28mm)

Pneumatic Ball Joint Service Tools

1996 Pneumatic Ball Joint Fork

Separates the ball joint from the steering knuckle.

Opening: 15/16"(24mm) *Length:* 7.1/2"(190mm)

Shank diameter: .401"Parker Shank

1985 Pneumatic Idler Arm Bushing Cutter

Tool is designed with a high cutting angle to cut bushes from idler arms. Also works well on other bushes and general cutting applications.

Length: 6"(150mm)

Shank diameter: .401"Parker Shank

1986 Pneumatic Control Arm Bush Remover

The concave design will hold the cutting edge against the bushing to remove control arm bushes easily.

Length: 6"(150mm)

Shank diameter: .401"Parker Shank

Pneumatic Punches

1983 Straight Solid Punch 1/2" Diameter

Use for peening and crimping bodies, driving rivets and hinge pins, plus many other punching applications.

Length: 6"(150mm)

Shank diameter: .401"Parker shank

Diameter: 1/2"(13mm)



1983

1997 Taper Punch 1/8" Point

1/8"(3mm) Taper punch will drive out rivets and pins.

Length: 6"(150mm)

Shank diameter: .401"Parker shank



1997

1982 Taper Punch 3/8" Point

Use for peening and crimping bodies, driving rivets and hinge pins, plus many other punching applications.

Length: 6"(150mm)

Shank diameter: .401"Parker shank



1982

1989 Long Taper Punch 1/8" Point

Extra long 1/8"(3mm) Taper punch for driving out rivets and pins.

Length: 18"(460mm)

Shank diameter: .401"Parker shank



1989

Pneumatic Nut Splitters

Ideal for removing seized locking clamps on tie rod adjuster sleeves, exhaust flange nuts and shock absorber nuts etc.

1993 6"Nut Splitting Tool

Length: 6"(150mm)

Shank diameter: .401"Parker shank

Opening: 5/16"(8mm)



1993

1994 10"Nut Splitting Tool

Length: 10"(250mm)

Shank diameter: .401"Parker shank

Opening: 3/8"(10mm)



1994


Pneumatic Service Tools

Turn with a wrench, the Shake & break action frees the toughest bolts & nuts including stubborn Torx-r fasteners.

1968 3/8" Drive Pneumatic Bolt Buster

Length: 6.1/2"(165mm)

Shank diameter: .401"Parker shank



1968

1969 1/2" Drive Pneumatic Bolt Buster

Length: 6.1/2"(165mm)

Shank diameter: .401"Parker shank



1969

1977 Pneumatic Exhaust Pipe Remover

Designed to separate muffler and tailpipe joints without causing damage to the inner section.

Length: 8"(200mm)

Shank diameter: .401"Parker shank



1977

1984 Pneumatic Hammer Head

Excellent for hammering operations such as body form work, uni-joint, ball joints, tie rod ends etc.

Length: 3.1/2"(90mm)

Shank diameter: .401"Parker shank

Head diameter: 1"(25mm)



1984

1995 Pneumatic Tie Rod Fork

Separates tie rod ends and shock absorber links.

Length: 7.1/2"(190mm)

Shank diameter: .401"Parker Shank

Opening: 21/32"(17mm)



1995

1987 Pneumatic Tie Rod Sleeve Breaker

Hammer action against the tie rod assembly loosens frozen sleeves to allow for easy adjustment.

Length: 3.1/2"(90mm)

Shank diameter: .401"Parker Shank



1987



*Far superior to
conventional air
chisel spring retainers*



1999



2000



8220




2001



2002



2007




6912-L

*Adjustable
Air Jet Nozzle*



G602



6912

Air Tool Accessories

1999 Pneumatic Tool Retainer Spring

Retains air chisels with .401"Parker shanks. Chisels can be installed and removed quickly by depressing the large diameter retaining loop.

2004 Heavy-Duty Air Chisel Retaining Chuck

Quick release chuck with four retaining ball bearings for positive retention of air chisels to air hammer gun. For use with Parker .401"shanks.

8220 1/4" & 3/8" Drive Jacobs Chuck Kit

Converts your 1/4" & 3/8" air ratchets into angle head drills

Kit includes both 1/4" x 1/4" drive & 3/8" x 3/8" drive Jacobs Chucks, chuck key and 1/4" hex x 1/4" drive adaptor. Uses include: drilling, tapping, hole sawing and stud removal in tight areas.

Supplied in plastic blow mold case.

2001 Air Pressure Regulator

Control air pressure as needed. Increase or decrease pressure as the job dictates.

Openings: 1/4"NPT Male and Female

2002 Air Pressure Regulator with Gauge

Control air pressure as needed. Increase or decrease pressure as the job dictates.

Openings: 1/4"NPT Male and Female

Gauge pressure: 0 to 160psi (0 to 11kg/cm²)

Gauge diameter: 1.1/2"(38mm)

2007 In-Line Water Separator

Removes water and foreign particles from compressed air stream. Attaches directly to spray gun or air tool. Clear reservoir shows accumulated water taken out of air line. Button release valve allows for easy disposal.

Filter can be removed and cleaned periodically.

Orifices: 1/4"NPT Male inlet x 1/4"NPT Female outlet

6912-L Long Reach Air Blow Gun

Industrial quality nylon body blow gun with copper parts & stainless steel spring. Sensitive trigger operation.

Length: 16"(400mm) **Inlet:** 1/4"NPT

G602 Two Way Air Duster

Extra heavy duty blow gun features top & bottom inlet for use with overhead hoses. Adjustable jet nozzle with exchangeable extension nozzle. All steel construction, includes Nitto type air fitting. **Extension Length:** 4.3/4"(120mm)

6912 Air Dust Gun

Professional all metal construction blow gun having trigger control from a whisper to full line pressure.

Trigger operates a spring loaded valve that has no cut offs or restrictions.

Ideal for carburetors, cylinders, brakes etc.

Length: 7.1/2"(190mm) **Inlet:** 1/4"NPT

G805 Engine Cleaning Gun

Multi-purpose cleaning gun is ideal for cleaning and degreasing engines etc. Also for applying fish oil and rust proofing products. Features a long shaft with an offset nozzle. Comes complete with 5ft(1.5m) gravity suction hose.

Operating air pressure: 70 to 80psi

Inlet: 1/4"BSP Male



G808 Sand Blasting Gun

Designed for fast effective sand blasting for removing or cleaning surfaces. Blast off rust, scale, carbon, chemicals or paint. Comes with 3ft(1m) hose with attachments.

Operating air pressure: 70 to 80psi

Inlet: 1/4"BSP Male



G806 Engine Cleaning Gun with Cup

Multi-purpose cleaning gun features a long nozzle with adjustable spray pattern and one litre metal container pot.

Operating air pressure: 70 to 80psi

Inlet: 1/4"BSP Male



G809 Sand Blasting Gun with Cup

Designed for fast effective sand blasting for removing or cleaning surfaces. Blast off rust, scale, carbon, chemicals or paint. Comes with one litre metal container pot.

Operating air pressure: 70 to 80psi

Inlet: 1/4"BSP Male



G933 Body Sealant Gun with Cup

Use for underbody treatment. Will spray a variety of fluids. Two extension probes for spraying into door cavities and sill panels. One to spray around corners and the other will spray 360 degrees around. Includes brass quick connect coupler and two flexible wands, one litre metal container pot.

Operating air pressure: 70 to 80psi

Inlet: 1/4"BSP Male



G936 Air Caulking Gun

Great for large volume work loads

Uses standard size cartridges 8.1/2" x 2"(215 x 50mm)

Operating air pressure: 30 to 40psi

Inlet: 1/4"BSP Male



G836 Hose Crimping Tool

This extra heavy-duty universal hose crimping tool will crimp with ease. Simply lift the handle and select the correct size, then push down for an accurate and reliable crimp every time.

Capacity: 7/16" to 3/4"(11 to 19mm) Diameter clamps


Length: 12"(300mm)

Weight: 10lb(4.5kg)

Male Nipple



Female Bush




Reducing Bush




End Plug



Three Way Tee (Male)



Three Way Tee (Female)



90° Female Elbow



NPT Male Nipples (Brass)

| Part No. | Size | Description | Length |
|----------|----------------|----------------------------|--------|
| X0404 | 1/8" x 1/8"NPT | Double End Male Nipple | 24.5mm |
| X0808 | 1/4" x 1/4"NPT | Double End Male Nipple | 26mm |
| X1212 | 3/8" x 3/8"NPT | Double End Male Nipple | 27mm |
| X1616 | 1/2" x 1/2"NPT | Double End Male Nipple | 31mm |
| X2424 | 3/4" x 3/4"NPT | Double End Male Nipple | 37.5mm |
| X0408 | 1/8" x 1/4"NPT | D/End Male Reducing Nipple | 25.5mm |
| X1208 | 3/8" x 1/4"NPT | D/End Male Reducing Nipple | 27mm |
| X1608 | 1/2" x 1/4"NPT | D/End Male Reducing Nipple | 29mm |
| X1216 | 3/8" x 1/2"NPT | D/End Male Reducing Nipple | 29mm |
| X2416 | 3/4" x 1/2"NPT | D/End Male Reducing Nipple | 35mm |

NPT Double Female Bushings (Brass)

| Part No. | Size | Description | Length |
|----------|----------------|---------------------------|--------|
| XF0404 | 1/8" x 1/8"NPT | Double End Female Bushing | 21mm |
| XF0808 | 1/4" x 1/4"NPT | Double End Female Bushing | 23mm |
| XF1212 | 3/8" x 3/8"NPT | Double End Female Bushing | 24mm |
| XF1616 | 1/2" x 1/2"NPT | Double End Female Bushing | 30mm |
| XF2424 | 3/4" x 3/4"NPT | Double End Female Bushing | 35mm |

NPT Male / Female Reducing Bushes (Brass))

| Part No. | Size | Description | Length |
|----------|----------------|-----------------------------|--------|
| X08F04 | 1/4" x 1/8"NPT | Male / Female Reducing Bush | 16mm |
| X12F08 | 3/8" x 1/4"NPT | Male / Female Reducing Bush | 16mm |
| X16F08 | 1/2" x 1/4"NPT | Male / Female Reducing Bush | 18mm |
| X16F12 | 1/2" x 3/8"NPT | Male / Female Reducing Bush | 18mm |
| X24F08 | 3/4" x 1/4"NPT | Male / Female Reducing Bush | 22mm |
| X24F12 | 3/4" x 3/8"NPT | Male / Female Reducing Bush | 22mm |
| X24F16 | 3/4" x 1/2"NPT | Male / Female Reducing Bush | 22mm |

NPT End Plug Nipples (Brass)

| Part No. | Size | Description | Length |
|----------|---------|-------------------------|--------|
| XP04 | 1/8"NPT | End Plug Nipple (Brass) | |
| XP08 | 1/4"NPT | End Plug Nipple (Brass) | |
| XP12 | 3/8"NPT | End Plug Nipple (Brass) | |
| XP16 | 1/2"NPT | End Plug Nipple (Brass) | |

NPT Three Way Male Tee (Brass)

| Part No. | Size | Description | Length |
|----------|---------|----------------------------|--------|
| XMT0404 | 1/8"NPT | Three Way Male Tee (Brass) | |
| XMT0808 | 1/4"NPT | Three Way Male Tee (Brass) | |
| XMT1212 | 3/8"NPT | Three Way Male Tee (Brass) | |
| XMT1616 | 1/2"NPT | Three Way Male Tee (Brass) | |

NPT Three Way Female Tee (Brass)

| Part No. | Size | Description | Length |
|----------|---------|------------------------------|--------|
| XFT0404 | 1/8"NPT | Three Way Female Tee (Brass) | |
| XFT0808 | 1/4"NPT | Three Way Female Tee (Brass) | |
| XFT1212 | 3/8"NPT | Three Way Female Tee (Brass) | |
| XFT1616 | 1/2"NPT | Three Way Female Tee (Brass) | |

90 Degree Female Elbow (Brass)

| Part No. | Size | Description | Length |
|----------|----------------|------------------------------|--------|
| XFE0404 | 1/8" x 1/8"NPT | Three Way Female Tee (Brass) | |
| XFE0808 | 1/4" x 1/4"NPT | Three Way Female Tee (Brass) | |
| XFE1212 | 3/8" x 3/8"NPT | Three Way Female Tee (Brass) | |
| XFE1616 | 1/2" x 1/2"NPT | Three Way Female Tee (Brass) | |

Nitto Type Air Fittings



No.NPF08
Male-Half Quick Release Coupling
with 1/4"NPT Female Thread



No.NBF08
Female-Half Quick Release
Coupling with
1/4"NPT Female Thread

Nitto Type Air Fittings



No.NPM08
Male-Half Quick Release Coupling
with 1/4"NPT Male Thread



No.NBM08
Female-Half Quick Release
Coupling with
1/4"NPT Male Thread


Nitto Type Air Fittings



No.NPT08
Male-Half Quick Release Coupling
with 5/16"Hose Tail Barb



No.NBT08
Female-Half Quick Release
Coupling with
5/16"Hose Tail Barb



No.PU10A
10 Metre Recoil Air Hose

Tradesman quality recoil air hose.
Features hose spring protector on
each end for longer hose life.

Threads: 1/4"NPT
Internal Dia.: 5/16"(8mm)
External Dia.: 1/2"(12mm)
Length: 32ft(10m)

No.PU20A
20 Metre Recoil Air Hose

Tradesman quality recoil air hose.
Features hose spring protector on
each end for longer hose life.

Threads: 1/4"NPT
Internal Dia.: 5/16"(8mm)
External Dia.: 1/2"(12mm)
Length: 64ft(20m)

Material: PU (Poly-Urethane)
Working Pressure: 120psi (8kg/cm2)
Burst Pressure: 240psi(20kg/cm2)

Nitto Type Air Fittings



No.NPU08
Male-Half Quick Release Coupling
with 5/16"Hose Union



No.NBU08
Female-Half Quick Release
Coupling with
5/16"Hose Union




No.JS6
Air Pressure Controller

Fitted with Nitto type male and female couples, this air pressure controller regulates air pressure by simply turning the control ring. (Not to exceed 400 P.S.I.)



No.MK1312A
2 Way Air Coupler

1/4NPT inlet with twin outlets fitted with Nitto type female couplers.



No.JS13
**360 Degree Swivel
Air Hose Leader**


1/4NPT leader Hose features a 360° swivel coupling to enable your air tool to reach into all angles. A leader hose allows air tools to operate more efficiently by eliminating the air coupling from being close to the air intake.



No.JS7
Air Speed Controller
1/4NPT male and female threads with
revolving air speed control switch.



Tradesman quality retractable air hose reel. Features protected hose storage and spring protection on the ends of the hose



Hose Temperature Range: -40° to 70° Celsius

Hose Working Pressure: 180psi(15Kg/cm²) Burst Pressure: 600psi(50kg/cm²)

**No.QS-2123A
10M Retractable
Air Hose Reel**

Threads: 1/4"NPT Male
Internal Dia.: 5/16"(8mm)
External Dia.: 1/2"(12mm)
Length: 32ft(10m)

**No.QS-2123B
12M Retractable
Air Hose Reel**

Threads: 1/4"NPT Male
Internal Dia.: 5/16"(8mm)
External Dia.: 1/2"(12mm)
Length: 39ft(12m)

**No.QS-2123C
15M Retractable
Air Hose Reel**

Threads: 1/4"NPT Male
Internal Dia.: 5/16"(8mm)
External Dia.: 1/2"(12mm)
Length: 49ft(15m)



**No.2005
Air Regulator with Gauge**

Features infinite adjustment of air pressure with 1/4"NPT inlet and outlet ports. Supplied with mounting bracket.
Gauge Readings: 0 to 150psi (0 to 10bar)
Gauge Diameter: 1.1/2"(38mm)



**No.2006
Air Filter Regulator
with Gauge**

Features infinite adjustment of air pressure with 1/4"NPT inlet and outlet ports. Fine micron filter removes moisture and impurities from the compressed air line. Supplied with mounting bracket and quick pull drain valve on filter bowl.
Gauge Readings: 0 to 150psi (0 to 10bar)
Gauge Diameter: 1.1/2"(38mm)



**No.2010
Air Filter
Regulator
with
Lubricator**

Features infinite adjustment of air pressure with 1/4"NPT inlet and outlet ports. Fine micron filter removes moisture and impurities from the compressed air line. Oil lubricator with flow adjustment valve to control the exact amount of oil lubricant required. Supplied with mounting bracket and quick pull drain valve on filter bowl.
Gauge Readings: 0 to 150psi (0 to 10bar)
Gauge Diameter: 1.1/2"(38mm)



**3 Metre air hose and
bracket assembly
with air fittings**

**No.JS812
Portable Compressed Air Tank**

Portable light weight air tank enables you to take compressed air on site. Simply charge tank with compressed air from any air compressor source. Tank holds 20 litres of compressed air at 15kg/cm² (180psi) Includes fully adjustable regulator, inlet and outlet hose couplings. 2"(50mm) Pressure gauge 15kg/cm² (180psi), 3 metre air hose and safety valve.
Weight: 28lb.(12.5kg) **Width:** 9"(230mm) **Height:** 13"(340mm) **Length:** 22"(550mm)



**No.JS8
100cc Air Tool Oil**

One hundred cubic centimeter dispenser of air tool oil for maintenance of air operated impact wrenches, drills, etc.

Twin Hammer Clutch
Max 200ft/lbs (271Nm)
4 Torque Control
Settings



No.QS-603N 3/8"Drive Lightweight Impact Wrench

A midget size twin hammer, low noise, high torque impact wrench. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 200ft/lb (271Nm)
Air Consumption: 3.5cfm
Air Pressure: 90psi
Air Inlet Size: 1/4"NPT
Weight: 2.9lb.(1.3kg)

Twin Hammer Clutch
Max 300ft/lbs (410Nm)
4 Torque Control
Settings



No.QS-603 3/8"Drive Lightweight Impact Wrench

A midget size twin hammer, low noise, high torque impact wrench. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 300ft/lb (410Nm)
Air Consumption: 3.5cfm
Air Pressure: 90psi
Air Inlet Size: 1/4"NPT
Weight: 3.3lb.(1.5kg)

Twin Hammer Clutch
Max 300ft/lbs (410Nm)
4 Torque Control
Settings



No.QS-604 1/2"Drive Lightweight Impact Wrench

A midget size twin hammer, low noise, high torque impact wrench. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 300ft/lb (410Nm)
Air Consumption: 3.5cfm
Air Pressure: 90psi
Air Inlet Size: 1/4"NPT
Weight: 3.3lb.(1.5kg)

Twin Hammer Clutch
Max 800ft/lbs (1100Nm)
4 Torque Control
Settings



No.QS-800 1/2"Drive Heavy Duty Composite Impact Wrench

A lightweight, heavy duty composite impact wrench with twin hammer, low noise and high torque. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 800ft/lb (1100Nm)
Air Consumption: 4.5cfm
Air Pressure: 90psi
Air Inlet Size: 1/4"NPT
Weight: 4.8lb.(2.18kg)

Twin Hammer Clutch
Max 800ft/lbs (1100Nm)
4 Torque Control
Settings



No.QS-1100 3/4"Drive Heavy Duty Impact Wrench

A lightweight, heavy duty impact wrench with twin hammer, low noise and high torque. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 800ft/lb (1100Nm)
Working range Torque: 50 to 800ft/lb (68 to 1100Nm)
Air Consumption: 4.5cfm
Air Pressure: 90psi
Air Inlet Size: 1/4"NPT
Weight: 5.2lb.(2.32kg)



No.QS-601N-2 (2" Anvil) 1"Drive Heavy Duty Impact Wrench

A heavy duty impact wrench with twin hammer, low noise and high torque. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 2500ft/lb (3390Nm)
Air Consumption: 12cfm
Air Pressure: 90psi
Air Inlet Size: 1/2"NPT
Weight: 28.1lb.(12.8kg)




No.QS-601N-8 (8" Anvil) 1"Drive Heavy Duty Impact Wrench

A heavy duty impact wrench with twin hammer, low noise and high torque. Includes a four speed control knob on the bottom of the handle to control the torque settings.

Maximum Torque: 2500ft/lb (3390Nm)
Air Consumption: 12cfm
Air Pressure: 90psi
Air Inlet Size: 1/2"NPT
Weight: 30.8lb.(13.9kg)





**Extracting & Filling
Pneumatic Oil Pump**

QS-2115 6Litre Pneumatic Oil Pump

New pneumatic fluid pump for extracting or filling of engine oil, coolant, transmission oil etc. Lock on air trigger for continuous use.
Air Line Working Pressure: 90psi. @ 4cfm.

**Powerful suction for
extracting oil is controlled
by adjusting regulator.**



QS-2117 Pneumatic Oil Extraction Pump

Used for extracting oil in machines, transmissions and oil containers. Features a built in regulator to control the pressure and flow while extracting or draining. Two way valve for suction and pressure.
Capacity: 6Litres



QS-2101

**Will extract 5 litres
of fluid within
3 minutes.**

fluid inlet **fluid outlet**

- Engine oil from crankcases
- Brake fluid from master cylinders
- Gear oil from transmission cases
- Coolant from cooling systems
- Power steering fluid from pump reservoirs
- And so much more

**Hand Pump Operation
requires no compressed
air or electrical supply.**

No.L7500 Fluid Evacuator Plus

Multi-purpose hand operated pressure and vacuum pump, provides a clean, fast and simple way to evacuate and dispense a wide range of fluids: engine oil, transmission fluid, gear oil, radiator coolant, brake fluid etc.



Features dip stick tubes for engine oil removal, automatic shut-off valve to prevent over filling. Can be used for either vacuum or pressure brake bleeding. Durable polyethylene construction is impervious to most automotive and general fluids. This rugged hand pump has proved to be indispensable for field work as it requires no compressed air or electrical supply.
Capacity: 7.3Litres

QS-2119 Air Washing Foam Sprayer

Air operated foam sprayer weighs less than 2kg and makes it easy to completely cover the vehicle with foam spray without using any excess water. Provides a quick, safe and easy method in car washing and cleaning.

Maximum capacity: 6000cc.

Air inlet: 1/4" NPT

Working Pressure: 30 - 140 PSI

Temperature range: 32F ~ 140F (0 ~ 60 c)



QS2114 Air Wax Sprayer

Air operated wax sprayer weighs less than 1.3kg and makes it easy to completely cover the vehicle with wax spray. Includes two 0.5m hoses and nozzles, one straight and one 90° for reaching into narrow space areas. Provides a quick, safe and easy method in car detailing and cleaning.

Maximum capacity: 2000cc.

Air inlet: 1/4" NPT

Working Pressure: 30 - 100 PSI

Temperature range: 32F ~ 140F (0 ~ 60 c)

